

NorGeoSpec 2012 Product Certificate



Certificate no.: 0108-QC-1419

Manufacturer: JUTA a.s.

Raw material: PP

Date: 01.08.14

Product: geoNETEX NGS 1

Function: Separation and Filtration

Valid until: 31.07.16

Product Type: GTX-N

Quality Product Certification Separation and Filtration

Characteristic	Standard	Unit	Declared value	Max. tolerance	Certification value	
Mass per unit	EN ISO 9864	g/m ²	95	± 11.4	84 - 106	
Mechanical tests						
Tensile strength	MD	EN ISO 10319	kN/m	6.20	- 0.62	6.10
	CMD	EN ISO 10319	kN/m	7.30	- 0.73	
Elongation at max. load	MD	EN ISO 10319	%	40.0	- 8.0	40.0
	CMD	EN ISO 10319	%	60.0	- 12.0	
Static puncture test	EN ISO 12236	kN	1.200	- 0.120	1.080	
Dynamic perforation resistance	EN ISO 13433	mm	30	+ 8	38	
Energy index	NorGeoSpec 2012	kN/m	1.2	-	1.2	
Hydraulic tests						
Velocity index	EN ISO 11058	m/s	0.090	- 0.027	0.063	
Characteristic opening size	EN ISO 12956	µm	90	± 27	63 - 117	
Durability (Declared value)						
Service life		years	<input checked="" type="checkbox"/> 25	<input type="checkbox"/> 50	<input type="checkbox"/> 100	

Quality Product Specification

Separation and Filtration

Application profile: **1**

Issued by

Christian Recker, NorGeoSpec project manager

Approved by

Arnstein Watn, Head of the Technical committee



The products are regularly audited and tested to verify that the characteristics fulfil the NorGeoSpec requirements.
Approved by the NorGeoSpec Technical committee: 01.08.14