

NorGeoSpec 2002 Product Certificate



Product Certificate

www.norgeospec.org

No 0905-QC-1244

PF15

NorGeoSpec 2002

Date:	2009-05-11
Valid until:	2011-05-11
Manufacturer:	Propex Inc.
Product:	PF15
Applicable to specification profile:	3
Certificate	No 0905-QC-1244
Certification procedure:	QC
Required level of delivery control: 1 identification test for every 50000 m ² , but minimum 1 id.test for deliveries over 10 000 m ²	

Characteristic		Maximum tolerance (units)	Declared tolerance ¹	Declared value ¹	95% confidence limit ²	Certification value
Tensile strength	MD kN/m	-1,6	-1,5	15,6	14,1	
EN ISO 10319	CMD kN/m	-1,8	-1,7	17,7	16,0	15,1
Tensile strain	MD %	-12,0 %	-12 %	60 %	48,0 %	
EN ISO 10319	CMD %	-12,0 %	-12 %	60 %	48,0 %	48,0 %
Cone drop diam						
EN 918	mm	4	4,4	22	26	26
Energy index						
EN ISO 10319	kN/m		0,0	3,2	3,2	3,2
Velocity index						
EN ISO 11058	10 ⁻³ m/s	-21	-21	70	49	49
Opening size						
EN ISO 12956	O ₉₀ (mm)	0,027	0,027	0,090	0,117	0,117
Mass EN ISO 9864 ³	g/m ²	25	25	245	221 - 270	221 - 270
Static puncture						
EN ISO 12236 ³	N	-250	-250	2500	2250	2250
Application profile						3

¹Mean values and tolerances given on a CE document with revision date: 13 March 2009
The CE document is approved by Notified body ID no: 0799

²The maximum tolerance is applied for determination of the 95% conf. limit when tolerances given on the CE-mark document exceeds the maximum allowable tolerance required in NorGeoSpec 2002. The products are continuously audited to verify that the characteristics fulfils the NorGoeSpec requirements.

³The certification values for these characteristics is to be used in delivery control. For the mass per unit area the allowable variation range is given while the minimum value is given for the static puncture strength.

SINTEF is **Notified as a competent body** related to directive 89/106/EEC by the Norwegian Royal Ministry of Trade and Industry

Notified body ID no: 1071

Products: Geotextiles and geotextile related products

Tasks: Inspection/Certification

Approved by the NorGeoSpec Technical committee 2009-05-11	Issued by	Approved by
	Hanne Louise Moe	Arnstein Watn

SINTEF Rock Engineering
NO-7465 Trondheim, NORWAY

Tlf + 47 73 59 46 00
Fax + 47 73 59 71 36