

NorGeoSpec 2002 Product Certificate



Product Certificate

www.norgeospec.org

No 1005-QC-1283

NG2NW

NorGeoSpec 2002

Date:	2010-05-21
Valid until:	2012-05-21
Manufacturer:	Thrace Nonwovens and Geosynthetics SA
Product:	NG2NW
Applicable to specification profile:	2
Certificate	No 1005-QC-1283
Certification procedure:	QC
Required level of delivery control: 1 identification test for every 50000 m ² , but minimum 1 id.test for deliveries over 10 000 m ²	

Characteristic		Maximum tolerance (units)	Declared tolerance ¹	Declared value ¹	95% confidence limit ²	Certification value
Tensile strength	MD kN/m	-1,1	-1,0	10,5	9,5	
EN ISO 10319	CMD kN/m	-1,2	-1,0	12,0	11,0	10,3
Tensile strain	MD %	-9,0 %	-9 %	45 %	36,0 %	
EN ISO 10319	CMD %	-10,0 %	-9 %	50 %	41,0 %	38,5 %
Cone drop diam						
EN 918	mm	6	6	30	36	36
Energy index						
EN ISO 10319	kN/m		0,0	2,1	2,1	2,1
Velocity index						
EN ISO 11058	10 ⁻³ m/s	-36	-36,0	120	84	84
Opening size						
EN ISO 12956	O ₉₀ (mm)	0,027	0,027	0,090	0,117	0,117
Mass EN ISO 9864 ³	g/m ²	16	-13	130	114 - 146	114 - 146
Static puncture						
EN ISO 12236 ³	N	-180	-180	1800	1620	1620
Application profile						2

¹Mean values and tolerances given on a CE document with revision date: The CE document is approved by Notified body ID no: 2010-02-04 1213

²The maximum tolerance is applied for determination of the 95% conf. limit when tolerances given on the CE-mark document exceeds the maximum allowable tolerance required in NorGeoSpec 2002. The products are continuously audited to verify that the characteristics fulfils the NorGoeSpec requirements.

³The certification values for these characteristics is to be used in delivery control. For the mass per unit area the allowable variation range is given while the minimum value is given for the static puncture strength.

SINTEF is **Notified as a competent body** related to directive 89/106/EEC by the Norwegian Royal Ministry of Trade and Industry

Notified body ID no: 1071

Products: Geotextiles and geotextile related products

Tasks: Inspection/Certification

Approved by the NorGeoSpec Technical committee 2010-05-21	Issued by	Approved by
	Maj Gøril Bæverfjord	Arnstein Watn