

NorGeoSpec 2012 Product Certificate



Certificate no.: NGS-50007 Manufacturer: Byggros A/S Raw material: PP
 Date: 31.01.2016 Product: BG-TEX NGS5 Function: Separation and Filtration
 Valid until: 30.01.2018 Product Type: GTX-N

Quality Product Certification Separation and Filtration

Characteristic	Standard	Unit	Declared value	Max. tolerance	Certification value
Mass per unit area	EN ISO 9864	g/m ²	355	± 36	320-391

Mechanical tests

Tensile strength	MD	EN ISO 10319	kN/m	29.00	- 2.90	26.10
	CMD	EN ISO 10319	kN/m	29.00	- 2.90	
Elongation at max. load	MD	EN ISO 10319	%	45.0	- 9.0	40.5
	CMD	EN ISO 10319	%	55.0	- 10.0	
Static puncture test		EN ISO 12236	kN	5.000	0.500	5.500
Dynamic perforation resistance		EN ISO 13433	mm	10	+ 2	12
Energy index		NorGeoSpec 2012	kN/m	6.5	0.0	6.5

Hydraulic tests

Velocity index		EN ISO 11058	m/s	0.030	- 0.009	0.021
Characteristic opening size		EN ISO 12956	µm	70	± 21	49-91

Durability (Declared value)

Service life			years	25		
--------------	--	--	-------	----	--	--

Quality Product Specification

Separation and Filtration	Application profile: 5
---------------------------	-------------------------------

Issued by

Christian Recker, NorGeoSpec project manager

Approved by

Arnstein Watn, Head of the Technical committee



The products are regularly audited and tested to verify that the characteristics fulfil the NorGeoSpec requirements.
 Approved by the NorGeoSpec Technical committee: 31.01.2016